according to UK REACH Regulation

DruckWege Type D Standard Rev. 3

Revision date: 12.05.2022 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DruckWege Type D Standard Rev. 3

UFI: Q300-P0FV-W00Q-GUYS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

3D Printing resin

Uses advised against

Not for intraoral area.

1.3. Details of the supplier of the safety data sheet

Company name: DruckWege BV Street: Wasaweg 1a

Place: NL-9723JD Groningen
Telephone: +31 50 7630845

e-mail: support@druckwege.com

Contact person: Rolf Meijer

Internet: www.druckwege.com

1.4. Emergency telephone +31 50 7630845 Only available during office hours.

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

hexamethylene diacrylate; hexane-1,6-diol diacrylate

Hexane, 1,6-diisocyanato-, polymers with 2-hydroxyethyl acrylate-blocked 1,6-diisocyanatohexane

 $homopolymer, 2-hydroxyethyl\ acrylate-\ and\ pentaerythritol\ triacrylate-blocked$

pentaerythritol tetraacrylate

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Signal word: Danger

Pictograms:







Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

according to UK REACH Regulation

DruckWege Type D Standard Rev. 3 Revision date: 12.05.2022 Page 2 of 12

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Dispose of waste according to applicable legislation.

Special labelling of certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional

use.

2.3. Other hazards

P310 P501

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)	•		
13048-33-4	hexamethylene diacrylate; hexane-	-1,6-diol diacrylate		50 - 100 %	
	235-921-9	607-109-00-8	01-2119484737-22		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. H411	1, Aquatic Acute 1, Aquatic Chronic 2	2; H315 H319 H317 H400		
2123508-19-8	Hexane, 1,6-diisocyanato-, polymers with 2-hydroxyethyl acrylate-blocked 1,6-diisocyanatohexane homopolymer, 2-hydroxyethyl acrylate- and pentaerythritol triacrylate-blocked			25 - 50 %	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317				
4986-89-4	pentaerythritol tetraacrylate				
	225-644-1	607-122-00-9			
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 2; H302 H315 H318 H317 H411				
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide				
	278-355-8	015-203-00-X			
	Repr. 2, Skin Sens. 1B, Aquatic Chronic 2; H361f H317 H411				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
13048-33-4	235-921-9	hexamethylene diacrylate; hexane-1,6-diol diacrylate	50 - 100 %	
	dermal: LD50 = 3650 mg/kg; oral: LD50 = 5000 mg/kg			
4986-89-4	225-644-1	pentaerythritol tetraacrylate	1 - 10 %	
	oral: ATE = 500 mg/kg			
75980-60-8	278-355-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	1 - < 3 %	
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg			

according to UK REACH Regulation

DruckWege Type D Standard Rev. 3

Revision date: 12.05.2022 Page 3 of 12

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

If unconscious but breathing normally, place in recovery position and seek medical advice.

When in doubt or if symptoms are observed, get medical advice.

In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

In the case of bluish discoloration (lips, earlobes, finger nails) give oxygen as soon as possible.

If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician. Call a doctor if you feel unwell.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye. Consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable. In case of fire may be liberated: Gases/vapours, toxic

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

according to UK REACH Regulation

DruckWege Type D Standard Rev. 3

Revision date: 12.05.2022 Page 4 of 12

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Further information on handling

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Store in a dry place. Provide adequate ventilation as well as local exhaustion at critical locations.

Hints on joint storage

No information available.

Further information on storage conditions

Protect against: UV-radiation/sunlight, Humidity.

7.3. Specific end use(s)

3D Printing resin

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

according to UK REACH Regulation

DruckWege Type D Standard Rev. 3

Revision date: 12.05.2022 Page 5 of 12

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide				
Worker DNEL, long-term inhalation systemic 3,5 mg/m³			3,5 mg/m³		
Worker DNEL, long-term dermal systemic 1 mg/kg bw/day			1 mg/kg bw/day		

PNEC values

CAS No	Substance		
Environmental	Environmental compartment		
75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			
Freshwater		0,004 mg/l	
Freshwater (intermittent releases)		0,035 mg/l	
Freshwater sediment		0,029 mg/kg	
Marine sediment		0,029 mg/kg	
Soil		0,056 mg/kg	

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls







Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Wear protective gloves.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Thermal hazards

No information available.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

according to UK REACH Regulation

DruckWege Type D Standard Rev. 3

Revision date: 12.05.2022 Page 6 of 12

Colour: various
Odour: like: Acrylate
Odour threshold: not determined

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

> 100 °C

boiling range:

Flash point: > 110 °C

Flammability

Solid/liquid: not applicable
Gas: not applicable

Explosive properties

The product is not: Explosive.

Lower explosion limits: not determined Upper explosion limits: not determined Auto-ignition temperature: > 230 °C

Self-ignition temperature

Solid:
Gas:
not applicable
not applicable
not applicable
not applicable
not determined
pH-Value:
not determined
Viscosity / dynamic:
not determined
Viscosity / kinematic:
not determined
Viscosity / konematic:
not determined
viscosity / poorly soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: < 1 hPa

(at 20 °C)

Density: not determined Relative vapour density: not determined

9.2. Other information

Other safety characteristics

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Protect against: UV-radiation/sunlight, Humidity.

according to UK REACH Regulation

DruckWege Type D Standard Rev. 3

Revision date: 12.05.2022 Page 7 of 12

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gases/vapours, toxic

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
13048-33-4	hexamethylene diacrylate; hexane-1,6-diol diacrylate					
	oral	LD50 5000 mg/kg	Rat	Manufacturer		
	dermal	LD50 3650 mg/kg	Rabbit	Manufacturer	OECD 402	
4986-89-4	pentaerythritol tetraacrylate					
	I = · ·	ATE 500 mg/kg				
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide					
	oral	LD50 > 5000 mg/kg	Rat	Manufacturer		
	dermal	LD50 > 2000 mg/kg	Rat	Manufacturer		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

Contains isocyanates. May produce an allergic reaction. May cause an allergic skin reaction. (hexamethylene diacrylate; hexane-1,6-diol diacrylate; Hexane, 1,6-diisocyanato-, polymers with 2-hydroxyethyl acrylate-blocked 1,6-diisocyanatohexane homopolymer, 2-hydroxyethyl acrylate- and pentaerythritol triacrylate-blocked; pentaerythritol tetraacrylate; diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

oral, Skin contact, Eye contact, Inhalation.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

Further information

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should

according to UK REACH Regulation

DruckWege Type D Standard Rev. 3

Revision date: 12.05.2022 Page 8 of 12

not be deployed in any process using this mixture.

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
13048-33-4	hexamethylene diacrylate	hexamethylene diacrylate; hexane-1,6-diol diacrylate					
	Acute bacteria toxicity	(EC50 mg/l)	270	0,5 h	Activated sludge	Manufacturer	OECD 209
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide						
	Acute algae toxicity	ErC50 mg/l	> 2,01	I . — · ·	Scenedesmus subspicatus	Manufacturer	
	Acute crustacea toxicity	EC50 mg/l	3,53		Daphnia magna (Big water flea)	Manufacturer	
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	Activated sludge	Manufacturer	

12.2. Persistence and degradability

The product has not been tested.

р						
CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation	-	-	-		
13048-33-4	hexamethylene diacrylate; hexane-1,6-diol diacrylate					
	OECD 310	60 - 70 %	28	Manufacturer		
Readily biodegradable (according to OECD criteria).						
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide					
	Biodegradation, Water	0 - 10 %	28	Manufacturer		
	Poorly biodegradable.					

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
13048-33-4	hexamethylene diacrylate; hexane-1,6-diol diacrylate	2,81
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	3,1

BCF

CAS No	Chemical name	BCF	Species	Source
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphi ne oxide	47 - 55	Cyprinus carpio (Common Carp) fish	Manufacturer

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

according to UK REACH Regulation

DruckWege Type D Standard Rev. 3

Revision date: 12.05.2022 Page 9 of 12

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

UN 3082 14.1. UN number or ID number:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 14.2. UN proper shipping name:

(hexamethylene diacrylate; hexane-1,6-diol diacrylate; pentaerythritol

tetraacrylate)

9

14.3. Transport hazard class(es):

Ш 14.4. Packing group:

Hazard label:



Classification code: M6

Special Provisions: 274 335 375 601

Limited quantity: 5 L Excepted quantity: E1 Transport category: 3 Hazard No: 90 Tunnel restriction code:

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 14.2. UN proper shipping name:

(hexamethylene diacrylate; hexane-1,6-diol diacrylate; pentaerythritol

tetraacrylate)

14.3. Transport hazard class(es):

9 Ш 14.4. Packing group: Hazard label:



Classification code: M6

Special Provisions: 274 335 375 601

Limited quantity: 5 L Excepted quantity: E1

Marine transport (IMDG)

UN 3082 14.1. UN number or ID number:

according to UK REACH Regulation

DruckWege Type D Standard Rev. 3

Revision date: 12.05.2022 Page 10 of 12

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(hexamethylene diacrylate; hexane-1,6-diol diacrylate; pentaerythritol

tetraacrylate)

9

Ш

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 9

Special Provisions: 274, 335, 969

Limited quantity: 5 L
Excepted quantity: E1
EmS: F-A. S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(hexamethylene diacrylate; hexane-1,6-diol diacrylate; pentaerythritol

tetraacrylate)

9

14.3. Transport hazard class(es):

14.4. Packing group:IIIHazard label:9



Special Provisions: A97 A158 A197

Limited quantity Passenger: 30 kg G Passenger LQ: Y964 Excepted quantity: E1

IATA-packing instructions - Passenger:964IATA-max. quantity - Passenger:450 LIATA-packing instructions - Cargo:964IATA-max. quantity - Cargo:450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: hexamethylene diacrylate; hexane-1,6-diol diacrylate; pentaerythritol

tetraacrylate

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to 2012/18/EU

(SEVESO III):

E1 Hazardous to the Aquatic Environment

according to UK REACH Regulation

DruckWege Type D Standard Rev. 3

Revision date: 12.05.2022 Page 11 of 12

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 3 - highly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 2; H411	Calculation method

according to UK REACH Regulation

DruckWege Type D Standard Rev. 3

Revision date: 12.05.2022 Page 12 of 12

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H361f Suspected of damaging fertility.
H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

EUH204 Contains isocyanates. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)